

# SHEEN ENHANCEMENT

## Universal Maintenance Oil

Application of Universal Maintenance Oil increases the sheen of Rubio® Monocoat's naturally matte Oil Plus 2C finish, providing additional design possibilities.

Universal Maintenance Oil Comes in 3 Colors:



The colors shown are on teak wood and are for reference only and are not binding.

## 0% VOC Maintenance For Non-Rubio Monocoat Surfaces

Annual or bi-annual maintenance of Non-Rubio® Monocoat oiled finishes is an absolute must to keep them well protected and to preserve color.

### Universal Maintenance Oil Provides:

- 0% VOC Maintenance
- Easy Application
- Quick Dry Time
- 3 Colors that can be blended
- Easier Care in the future with Rubio® Monocoat Care Products



## SheenPlus

For an oiled look with a higher sheen, SheenPlus offers a durable satin sheen for surfaces previously finished with Oil Plus 2C.

### SheenPlus Characteristics:

- 0% VOC
- Long-lasting satin finish
- Scratch-resistant result
- High spread rate
- No overlapping



# Rubio® MONOCOAT



**MUYLLE-FACON**  
A PASSION FOR WOOD TREATMENT SINCE 1962

Muylle Facon was founded in 1906 as a manufacturer of high-quality putty and is now an important producer of waterproof products, coatings and sealers, impermeable and impervious to water, and other specialties for buildings.

It's first range of wood treatment products was launched in 1962:

**Teintécire:** Waterbased colorstain with warm colors, which provides a nice gloss and antique look.

**Ciraneuf:** Liquid or solid beeswax, turpentine based.

**Boizaneuf:** Paint remover.

The close collaboration between the laboratory, the sales-team and the applicators has resulted in the development of the unique Rubio® Monocoat range.

\*Based on test method CMA/3/E

Rubio® is a Registered Trademark of Muylle-Facon.

0%  
VOC

# Rubio® MONOCOAT



## CARE AND MAINTENANCE

**SURFACE CARE SPRAY  
SOAP  
RENEW  
OIL PLUS 2C  
UNIVERSAL MAINTENANCE OIL  
SHEENPLUS**

# CLEANING

## Surface Care Spray

**Rubio® Monocoat Surface Care Spray** is the only recommended cleaner for your Rubio® Monocoat oil finished surface. It will remove all dirt and grease thoroughly, without leaving a film or affecting the matte natural look of the wood. It is suitable for both general cleaning and easy cleaning of localized stains.

**Rubio® Monocoat Surface Care Spray** is made by mixing **Rubio® Monocoat Soap** with water at a ratio of 1:100, respectively.

### CLEANING THE FINISH:

Once surface has fully cured, Rubio® Monocoat can be cleaned as follows:

1. **SWEEP, DUST, or DRY MOP.**
2. **DAMP MOP** the finish with water or **Rubio® Monocoat Surface Care Spray**.
3. **DO NOT USE ANY OTHER CLEANERS** as most of these will damage the finish.



Common Mixing Measurements

WATER	RMC SOAP
750 milliliter	1/2 tbsp
1 gallon	1.3 fluid oz



## WARNING!

DO NOT use any other cleaners  
DO NOT tape on Rubio® Monocoat  
DO NOT allow moisture on uncured Rubio® Monocoat treated surfaces (5 days to cure)

# MAINTENANCE

## Renew

**Rubio® Monocoat Renew** is a ready-to-use product that refreshes, restores and protects surfaces treated with Rubio® Monocoat Oil Plus 2C. Renew should be used when the surface feels too dry or rough, or when the finish has worn down due to heavy use.

**NOTE:** If color restoration is necessary, perform a 2C Renovation.

### RENEWING THE FINISH:

1. **CLEAN** the surface with **Rubio® Monocoat Surface Care Spray**.
2. **APPLY** **Rubio® Monocoat Renew** on the surface area.
3. **REMOVE ALL EXCESS OIL** within 10-15 minutes.
4. **WALKABLE AFTER 4-6 HOURS.**



### LOOKING FOR DETAILED CARE INSTRUCTIONS?



SCAN ME



# RENOVATION

## Oil Plus 2C Renovation

**Rubio® Monocoat Oil Plus 2C** can be used to renew and renovate a Rubio® Monocoat finished surface where color restoration is necessary.

### RENOVATING THE FINISH:

1. **CLEAN** with **Rubio® Monocoat Surface Care Spray**.
2. **ABRADE** the surface with a maroon pad.
3. **REMOVE** all dust from the surface.
4. **APPLY** **Rubio® Monocoat Oil Plus 2C** the same way you would an initial application.
5. **REMOVE ALL EXCESS OIL** within 15 minutes.



Renovating with Oil Plus 2C in the original color



Lightly abraded surface